


















HALEAD SVP Flooring

Technical Specification

Performance Attribute	Standard	Result
 Total Thickness	ISO 24346	5–8mm
Density	EN 430	1.5~1.6g/cm ³
Edge Straightness	EN427	≤0.10mm
Squareness	EN427	≤0.10mm
 Surface treatment	/	PUR
 Curling 80°C/6H	EN 434/ISO 23999	≤1.0mm
 Dimensional Stability (Shrinking 80°C/6H)	EN 434/ISO 23999	≤0.12%
 Residual Indentation	ISO 24343–1	≤0.10mm
	ASTM F1914	≤8%
 Slip Resistance	DIN 51130	R10
 Coefficient of Static Friction	ASTM D2047	Dry State ≥0.4
		Wet State ≥0.5
 Locking Strength	ISO 24334	≥120N/50mm
 Scratch Resistance	ISO1518	≥2500g
 Acoustic	EN ISO10140–1	△ LW 20
 Boiling Water 100°C/2H	EN438–2	No bubble, no delamination
 Light fastness	ISO 105–B02	≥Grade 6
 Castor Test	ISO4918	25000R No damage
 Fire Resistant Classification	EN 13501–1	Bfl–s1
Resistance to staining and chemicals	ISO 26987	Class 0
 Toxic Elements Analysis	EN71–3	Pass
 Phthalates Test	CPSC–CH–C1001–09.4	Pass
 Environmental	French VOC regulation (ISO 1600)	A+